Model POU1CCTHS Hot & Cold

Weight 13 kg

Dimensions (H x W x D) 45.5 cm x 31 cm x 36 cm

Performance (litres of cold water / hour)

Performance Specifications Inlet water at 22°C

' dispenses 6 litres of water below 10°C per hour

' dispenses 65 0.18 litre cups per hour of water below 10°C

Performance (litres of hot water / hour) 7.0

Refrigerant type R134a

Refrigerant charge 35 g

Cold tank capacity 2.0 litres

Hot tank capacity 1.2 litres

Power consumption 500 Watt

Model POU1CCTK Cook & Cold

Weight 12 kg

Dimensions (H x W x D) 45.5 cm x 31 cm x 36 cm

Performance (litres of cold water / hour)

Performance Specifications Inlet water at 22°C

' dispenses 6 litres of water below 10°C per hour


' dispenses 65 0.18 litre cups per hour of water below 10°C

Refrigerant type R134a
Refrigerant charge 35 g
Cold tank capacity 2.0 litres

Power consumption 85 Watt









Stylish design to match contemporary kitchen and break room decors

High end appearance

- > Metal side panels
- > Injection moulded front & top
- > Aluminum trim
- > Electronic faucets



Cold Water Reservoir:

Type 300 series stainless steel. External copper refrigerant coil. Encased in pre-fitted molded plastic foam insulation.



Electronic faucets:

Hot Water Safety Faucet - self closing faucet requires a two-step action that is easy for adults to use, but helps to protect small children.



One - Piece Hot Water Tank:

450 watt heating element. One piece tank is easy to replace or service without breaking soldered refrigeration connections. The hot tank is type 300 series stainless steel.



Drip Tray.

Moves out in seconds for easy sanitization. Lighted up with the diode.

